

AMENDMENTS TO THE CLAIMS:

30. (currently amended) An apparatus for coating substrates,
comprising:

a substrate holder for holding thereon a substrate in such a way that a surface of
said substrate that is to be coated is exposed and is directed downwardly;

a means for rotating said substrate holder; and

a cover that is securable to said substrate holder, such that the cover is freely
rotatable therewith, wherein said cover, together with said substrate holder, are adapted
to form a sealed chamber for receiving the substrate.

31. (previously added) An apparatus according to claim 30, wherein a holding
mechanism is provided on said substrate holder for holding the substrate by means of
vacuum.

32. (previously added) An apparatus according to claim 31, wherein a holding
mechanism is provided on said substrate holder for holding said cover by means of
vacuum.

33. (previously added) An apparatus according to claim 32, wherein said
holding mechanisms for the substrate and for said cover are connected to a common
vacuum source.

34. (previously added) An apparatus according to claim 32, wherein said
holding mechanisms for the substrate and for said cover are adapted to be controlled
independently of one another.

35. (previously added) An apparatus according to claim 32, wherein at least

one sealing means is provided for delimiting a vacuum region between said substrate holder and said cover.

36. (previously added) An apparatus according to claim 30, wherein said substrate holder is provided with a recess for an at least partial accommodation of the substrate.

37. (previously added) An apparatus according to claim 30, wherein a centering mechanism is provided for a mutual centering of said cover and said substrate holder.

C1
cont
38. (previously added) An apparatus according to claim 37, wherein said centering mechanism is in the form of at least one slanted centering portion on at least one of said substrate holder and said cover.

39. (previously added) An apparatus according to claim 30, wherein said cover is symmetrical relative to a central axis C thereof.

40. (previously added) An apparatus according to claim 30, wherein a notch is provided in an outer region of a portion of said cover that defines said chamber.

41. (previously added) An apparatus according to claim 40, wherein said notch tapers outwardly.

42. (previously added) An apparatus according to claim 40, wherein said notch is inclined on a side thereof that faces said substrate holder.

43. (previously added) An apparatus according to claim 39, wherein said cover is symmetrical relative to a central plane B thereof.

44. (previously added) An apparatus according to claim 30, wherein a device

is provided for turning said cover.

45. (previously added) An apparatus according to claim 40, wherein a receiver is provided for supporting said cover.

46. (previously added) An apparatus according to claim 45, wherein a device is provided for raising and lowering said receiver.

47. (previously added) An apparatus according to claim 45, wherein a rinsing and/or drying device is provided for said cover.

48. (previously added) An apparatus according to claim 47, wherein said rinsing and/or drying device is part of said receiver and is provided with at least one nozzle that is directed against at least one of said cover and said notch.

C1
wt
49. (previously added) An apparatus according to claim 48, wherein at least one nozzle is adapted to be supplied with a rinsing and/or drying fluid.

50. (previously added) An apparatus according to claim 49, wherein said rinsing fluid contains a solvent.

51. (currently amended) A method for coating substrates, including the steps of:

holding a substrate on a substrate holder in such a way that a surface of the substrate that is to be coated is exposed and is directed downwardly;

securing to said substrate holder a cover that together with said substrate holder forms a sealed chamber for receiving the substrate;

rotating the substrate together with said substrate holder and said cover.

52. (previously added) A method according to claim 51, wherein at least one

of the substrate and said cover is held or secured on said substrate holder by means of vacuum.

53. (previously added) A method according to claim 52, which includes the step of centering said cover and said substrate holder relative to one another prior to the holding or securement.

54. (previously added) A method according to claim 51, wherein after said step of rotating the substrate, the securement of said cover is released independent of the holding of the substrate.

55. (previously added) A method according to claim 51, wherein during said step of rotating the substrate a side of said cover that faces away from the substrate is rinsed and/or dried.

CI
at
56. (previously added) A method according to claim 51, wherein a rinsing or drying fluid is conveyed against said cover by means of at least one nozzle.

57. (previously added) A method according to claim 51, which includes the step of turning said cover between successive ones of said rotating steps.
